



Hi-Res Differential Manometer

KANE3300

Hi-Res Differential Manometer w/ Wide Measurement Range



Functions

- Accuracy: $\pm 0.03 < 3 \text{ inchH}_2\text{O}$, $\pm 1\% \text{rdg} > \text{inchH}_2\text{O}$
- Resolution: $0.001'' (-9.999 \text{ to } +9.999 \text{ inchH}_2\text{O})$, $0.01'' (< -10, > +10 \text{ inchH}_2\text{O})$

Features

- HOLD MIN/MAX/AVG
- Capture
- Ambient temperature measurement
- Backlight
- Auto Power off
- Low Battery Indicator
- 1-Year limited warranty

Includes

- Flexible Transparent Tubing
- Brass Fitting (2)
- Step connector w/ 3.15" tubing (2)
- Soft case
- Manual



Application

- Check gas pressures in accordance with equipment manufacturers specifications, Measure draft, gas supply, manifold or burner pressures, Dual input offers users the ability to measure pressure drops across heat exchangers, cooling coils, supply and return
- Check gas pressures in accordance with equipment manufacturers specifications
- Measure draft, gas supply, manifold or burner pressures
- Dual input offers users the ability to measure pressure drops across heat exchangers, cooling coils, supply and return registers and filters



Hi-Res Differential Manometer

KANE3300

Specifications

	KANE201B	KANE3300
Range	±60" WC	±80 InWC
Accuracy	±0.03"WC from 0 to 3" InWC, ±1 % rdg from 3" InWC to 60" InWC	±0.03 < 3 inWC, ±1%rdg > inWC
Resolution	0.001" -9.999" to +9.999" InWC, 0.01" for < -10" or > +10" InWC	0.001"(-9.999 to +9.999 inchH2O), 0.01" (< -10,> +10 inchH2O)
Differential Pressure	•	•
Hold	•	•
Dual Input	•	•
Min/Max/Avg	Min/Max	•
Record		Capture
Backlit display	•	•
Apo	•	•
Low Battery Indicator		•
Ambient Temperature Measurement		•
Temperature Compensation		•
Units of Measurement	3	12
Rubber Boot/Overmolding	•	•
Magnetic Mount	•	•
Zero		•
Warranty	1-Year limited	1-Year limited
Included	Pressure Tubes with brass fittings, 2 (BF100), Battery, Manual	Pressure Tubes with brass fittings, 2 (BF100), Case, Battery, Manual
Power Source	Battery 9V	Batteries 3 (AA)
Certifications	RoHS	UK CA, CE, FCC, RoHS. REACH Compliant

