



SK10 STARTER KIT



KANE3300
Dual Differential
Digital Manometer



KANE569
400A Dual Display Clamp
Meter w/ Test Lead Storage



KANE700
Combustible Gas Leak
Detector w/ 17.5 Inch
Gooseneck



PDT550
Digital Pocket
Thermometer NSF



⚠ WARNING: This product can expose you to chemicals including, Lead and lead compounds, Cobalt Lithium Nickel Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

⚠ ADVERTENCIA: Este producto puede exponerlo a productos químicos, incluido, Lead and lead compounds, Cobalt Lithium Nickel Oxide, que el estado de California sabe que causan cancer y defectos de nacimiento u otros daños reproductivos. Para más información, visite www.P65Warnings.ca.gov.

⚠ AVERTISSEMENT: Ce produit contient des produits chimiques y compris, Lead and lead compounds, Cobalt Lithium Nickel Oxide, reconnu par l'État de Californie pour être cancérigènes, provoquer des malformations congénitales ou d'autres troubles de l'appareil reproducteur. Pour davantage de renseignements allez sur www.P65Warnings.ca.gov.





Kit Includes

KANE569

400A Dual Display Clamp Meter
w/ Test Lead Storage

- 400A AC
- 1000V DC
- 750V AC
- 40 k Ω Resistance
- DC mV
- Audible Continuity
- Diode Test
- Non-Contact Voltage Detection
- Dual Display
- Test Lead Storage
- Min/Max/Hold
- High-voltage alert
- 1-Year limited warranty

KANE700

Combustible Gas Leak Detector w/ 17.5
Inch Gooseneck

- Sensitivity: <50 ppm methane
- 17.5 inch gooseneck
- Audible indicator: variable tic rate
- Visual indicator: Flashing multicolored LED's
- Response time: 20 sec.
- Sensor: Solid state semi conductor
- 1-Year limited warranty

KANE3300

Dual Differential Digital Manometer

- Accuracy: ± 0.03 < 3 inchH₂O, $\pm 1\%$ rdg > inchH₂O
- Resolution: 0.001"(-9.999 to +9.999 inchH₂O), 0.01" (< -10, > +10 inchH₂O)
- HOLD MIN/MAX/AVG
- Capture
- Ambient temperature measurement
- Backlight
- Auto Power off
- Low Battery Indicator
- 1-Year limited warranty

PDT550

Digital Pocket Thermometer

- Temperature range: -58° to 572°F (-50° to 300°C)
- Waterproof
- NSF
- Magnetic mount
- Min/Max
- 1-Year limited warranty

AC73

Soft Carrying Case (12 in x 15 in x 3.5 in)

- Customizable dividers
- Interior and exterior pockets
- Stylish design
- Carrying strap
- 1-Year limited warranty