



# SK20

## STARTER KIT



**KANE3300**  
Dual Differential  
Digital Manometer

**KANE579**  
600A True-RMS Dual Display  
HVAC/R Clamp Meter w/  
Temperature & Capacitance



**KANE700**  
Combustible Gas Leak  
Detector  
w/ 17.5 Inch Gooseneck



**ATTPC4**  
K-Type Pipe Clamp  
Probe (grip style)



**PDT550**  
Digital Pocket  
Thermometer NSF



**⚠ WARNING:** This product can expose you to chemicals including, Lead and lead compounds, Cobalt Lithium Nickel Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).  
**⚠ ADVERTENCIA:** Este producto puede exponerlo a productos químicos, incluido, Lead and lead compounds, Cobalt Lithium Nickel Oxide, que el estado de California sabe que causan cancer y defectos de nacimiento u otros daños reproductivos. Para más información, visite [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).  
**⚠ AVERTISSEMENT:** Ce produit contient des produits chimiques y compris, Lead and lead compounds, Cobalt Lithium Nickel Oxide, reconnu par l'État de Californie pour être cancérigènes, provoquer des malformations congénitales ou d'autres troubles de l'appareil reproducteur. Pour davantage de renseignements allez sur [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).





### Kit Includes

---

#### **KANE579**

600A True-RMS Dual Display HVAC/R  
Clamp Meter w/ Temperature & Capacitance

- TRMS 750/1000V
- AC/DC, 600A AC/DC
- AC/DC Microamps
- Dual Display
- Low Z (impedance)
- Resistance
- Continuity
- Diode test
- Frequency/Duty Cycle
- NCV
- Min/Max
- Data Hold
- 1-Year limited warranty

#### **KANE700**

Combustible Gas Leak Detector w/ 17.5  
Inch Gooseneck

- Sensitivity: <50 ppm methane
- 17.5 inch gooseneck
- Audible indicator: variable tic rate
- Visual indicator: Flashing multicolored LED's
- Response time: 20 sec.
- Sensor: Solid state semi conductor
- 1-Year limited warranty

#### **KANE3300**

Dual Differential Digital Manometer

- Accuracy:  $\pm 0.03 < 3 \text{ inchH}_2\text{O}$ ,  $\pm 1\% \text{rdg} > \text{inchH}_2\text{O}$
- Resolution:  $0.001'' (-9.999 \text{ to } +9.999 \text{ inchH}_2\text{O})$ ,  $0.01'' (< -10, > +10 \text{ inchH}_2\text{O})$
- HOLD MIN/MAX/AVG
- Capture
- Ambient temperature measurement
- Backlight
- Auto Power off
- Low Battery Indicator
- 1-Year limited warranty

#### **PDT550**

Digital Pocket Thermometer

- Temperature range:  $-58^\circ \text{ to } 572^\circ \text{F}$   
( $-50^\circ \text{ to } 300^\circ \text{C}$ )
- Waterproof
- NSF
- Magnetic mount
- Min/Max
- 1-Year limited warranty

#### **ATTPC4**

K-Type Pipe Clamp Probe (grip style)

- Temperature range:  $32^\circ \text{ to } 176^\circ \text{F}$  ( $0^\circ \text{ to } 80^\circ \text{C}$ )
- Fits  $3/16 \text{ inch}$  to  $1 \text{ } 7/16 \text{ inch}$  pipes
- Thermocouple temperature probe
- Compact and easy to use
- Thermally Insulated Sensor
- 1-Year limited warranty

#### **AC73**

Soft Carrying Case (12in x 15in x 3.5in)

- Customizable dividers
- Interior and exterior pockets
- Stylish design
- Carrying strap
- 1-Year limited warranty