



SK30

STARTER KIT



KANE3300KIT
Hi-Res Differential
Manometer
Static Pressure Kit



KANE589
600A True-RMS Dual Display
ClampMeter w/ DC Amps &
Differential Temperature



KANE700
Combustible Gas Leak
Detector
w/ 17.5 Inch Gooseneck



ATTPC4
K-Type Pipe Clamp
Probe (grip style)



PDT550
Digital Pocket
Thermometer NSF



⚠ WARNING: This product can expose you to chemicals including, Lead and lead compounds, Cobalt Lithium Nickel Oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

⚠ ADVERTENCIA: Este producto puede exponerlo a productos químicos, incluido, Lead and lead compounds, Cobalt Lithium Nickel Oxide, que el estado de California sabe que causan cancer y defectos de nacimiento u otros daños reproductivos. Para más información, visite www.P65Warnings.ca.gov.

⚠ AVERTISSEMENT: Ce produit contient des produits chimiques y compris, Lead and lead compounds, Cobalt Lithium Nickel Oxide, reconnu par l'État de Californie pour être cancérigènes, provoquer des malformations congénitales ou d'autres troubles de l'appareil reproducteur. Pour davantage de renseignements allez sur www.P65Warnings.ca.gov.





KANE589

600A True-RMS Dual Display Clamp Meter
w/ DC Amps & Differential Temperature

Functions

- 600A AC/DC
- 1000V DC
- 750V AC
- 2000 μ A AC/DC
- 60M Ω Resistance
- Capacitance: 6000 μ F
- Differential Temperature: -328° to 2462°F
- Frequency/Duty Cycle
- Audible Continuity

Features

- TRMS
- Backlit Dual Display and Worklight
- Min/Max/Avg/Hold
- Peak Hold
- Auto Volts & Amp selection
- Built-in Magnet w/ hanging strap
- Test Lead Storage
- Visible high-voltage alert
- Easy access battery cover latches
- Over-molded grip
- Auto and Manual ranging
- 2-Year limited warranty

KANE3300KIT

Hi-Res Differential Manometer
Static Pressure Kit

- Measures Pressure \pm 80 inWC
- Temperature compensation protects sensor accuracy from ambient temperature sources.
- HOLD
- MIN/MAX/AVG
- Capture
- Ambient temperature measurement
- Backlight
- Auto Power off
- Low Battery Indicator
- 1-Year limited warranty

KANE700

Combustible Gas Leak Detector w/ 17.5
Inch Gooseneck

- Sensitivity: <50 ppm methane
- 17.5 inch gooseneck
- Audible indicator: variable tic rate
- Visual indicator: Flashing multicolored LED's
- Response time: 20 sec.
- Sensor: Solid state semi conductor
- 1-Year limited warranty

PDT550

Digital Pocket Thermometer

- Temperature range: -58 \hat{u} to 572 \hat{u} F (-50 \hat{u} to 300 \hat{u} C)
- Waterproof
- NSF
- Magnetic mount
- Min/Max
- 1-Year limited warranty

ATTPC4

K-Type Pipe Clamp Probe (grip style)

- Temperature range: 32° to 176°F (0° to 80°C)
- Fits 3/16 inch to 1 7/16 inch pipes
- Thermocouple temperature probe
- Compact and easy to use
- Thermally Insulated Sensor
- 1-Year limited warranty

AC73

Soft Carrying Case (12 x 15 x 3.5)

- Customizable dividers
- Interior and exterior pockets
- Stylish design
- Carrying strap
- 1-Year limited warranty